




Nástenná vnútorná jednotka AERI | AERI | AENI



Model	ACP-07CH21AENI/I	ACP-09CH25AERI/I+	ACP-12CH35AERI/I+	ACP-18CH50AERI/I+	ACP-09CH25AERI/I+	ACP-12CH35AERI/I+	ACP-18CH50AERI/I+
Vnútorná jednotka							
Kapacita (W)	2052	2638	3517	5275	2638	3517	5275
Prevádzkový rozsah chladenia	-15 °C ≤ T ≤ 50 °C	-15 °C ≤ T ≤ 50 °C	-15 °C ≤ T ≤ 50 °C	-15 °C ≤ T ≤ 50 °C	-15 °C ≤ T ≤ 50 °C	-15 °C ≤ T ≤ 50 °C	-15 °C ≤ T ≤ 50 °C
Kapacita (W)	2346	2931	3810	5568	2931	3810	5568
Prevádzkový rozsah vykurovania	-20 °C ≤ T ≤ 24 °C	-20 °C ≤ T ≤ 24 °C	-20 °C ≤ T ≤ 24 °C	-20 °C ≤ T ≤ 24 °C	-20 °C ≤ T ≤ 24 °C	-20 °C ≤ T ≤ 24 °C	-20 °C ≤ T ≤ 24 °C
Prietok vzduchu (m³ / h) - HI / MID / LOW	430 / 330 / 280	483 / 362 / 303	584 / 477 / 395	730 / 500 / 420	700 / 515 / 425	700 / 515 / 425	750 / 530 / 430
Chladivo	R32	R32	R32	R32	R32	R32	R32
Kapacita odvlhčovania (L / h)	1,0	1,0	1,2	1,8	1	1,2	1,8
Hluk - Akustický tlak (dB (A)) - HI / MID / LOW / SI	37 / 32 / 24 / 21	36,5 / 29 / 24 / 20	39,5 / 33 / 25 / 21	43 / 33,5 / 28 / 23	40 / 32,5 / 21,5	40 / 32,5 / 21,5 / 19	41,5 / 36,5 / 33,5 / 19
Hlasitosť za štandardných podmienok (dB)	≤ 54	≤ 55	≤ 55	≤ 57	≤ 53	≤ 53	≤ 54
Rozmery balenia (mm)	790 x 270 x 375	875 x 285 x 380	875 x 285 x 380	1045 x 305 x 410	1005 x 295 x 385	1005 x 295 x 385	1005 x 295 x 385
Rozmery zariadenia (mm)	726 x 210 x 291	802 x 189 x 297	802 x 189 x 297	965 x 215 x 319	920 x 211 x 321	920 x 211 x 321	920 x 211 x 321
Brutto / netto váha (kg)	9,4 / 7,0	11,1 / 8,6	11,1 / 8,6	14,2 / 10,9	11,3 / 14,2	11,3 / 14,2	11,5 / 14,4
Pripojenie							
Priemer potrubia v kvapalnej fáze	1 / 4"	1 / 4"	1 / 4"	1 / 4"	1 / 4"	1 / 4"	1 / 4"
Priemer potrubia v plynnej fáze	3 / 8"	3 / 8"	3 / 8"	1 / 2"	3 / 8"	3 / 8"	1 / 2"
Prepojovací kábel							
Pripojenie (mm²)	4 x 1,5	4 x 1,5	4 x 1,5	4 x 1,5	4 x 1,5	4 x 1,5	4 x 1,5
Zdroj	~220-240 V / 1 / 50 Hz; Vonkajšia jednotka						